



## Performance Biolubricants and Colloidal Cleaners

### Food Grade Gear Oil (NSF H1, H2) ISO-46, SAE 30

#### Typical Specifications



Nonfood Compounds  
Program Listed (H1, H2)  
(Registration #140521)

WISE Food Grade (FG) Gear Oils are designed to meet or exceed OEM and equipment requirements for their respective SAE grades and API classifications. In addition to high performance, these gear oils are formulated from environmentally responsible, renewable, non-GMO agricultural plant resources.

We believe Earth's environmental future rests in the use of renewable materials.

WISE FG Gear Oils<sup>1</sup> is for gear drives and right angle gear drives commonly used in food processing equipment; this oil is essentially odorless and tasteless. These gear sets do not require Hypoid level of extreme pressure and because of this, the lubricant most commonly specified by makers of these gear reducers is an R&O or GL-3 type circulating oil.

WISE Solutions patented formula has improved performance over conventional products in terms of thermal shear and fluid film (viscosity index). This super high viscosity index allows this product to be energy conserving in the startup mode and provide improved load protection, reducing wear, during operation. It is highly inhibited against moisture and rusting in both fresh and seawater and passes both A and B Sequences of the ASTM D-665 Turbine Oil Rust Test. This product also provides double the oxidation stability over the US Steel 127 test requirement of 125 minutes and shows excellent performance in ASTM D-1401 Turbine Oil Demulsibility with a rating of 40/40/0 in ten minutes. WISE FG Gear Oil has stabilized base stock technology combined with specialized, food grade mild EP/anti-wear additives that exceed the load stage 10 in the FZG (DIN51354) requirements for both turbine oils and reduction gears. The result is a patented Food Grade product with long life heat stability and the protection advantages of the mild EP and antiwear of an API "GL-3" type gear lube.

API Gravity @ 60°F (D-287)	28.6
Pounds/Gallon @ 60°F	7.36
Specific Gravity @60°F (D-287)	.8838
VISCOSITIES:	
@100°C, cSt. (D-445)	9.31
@40°C, cSt. (D-445)	45.01
Viscosity Index (D-2270)	196
Flash Point, °C (D-92)	240.5°C, 465°F
Pour Point, °C (D-97)	-21
Copper Corrosion (D-130) 3hr @ 100°C	1B
Acid Number (D-974)	1.04
Demulsibility (D-1401) 10 minutes	40/40/0
Foam Sequence I, II, III (D-892) 10 minutes	0 Foam
Rust Prevention, (D-665 A&B)	Pass Clean
4 Ball Wear (D-4172), 1h, 167°F, 1200 RPM, 40kg	.34
Shell 4-Ball EP Test (D-2783)	
Weld Load/Load Wear Index	160-200/47
Timken OK Load Test (D-2782), 'OK' Load (lbs)	33/35
FZG Test (DIN 51517)	11
Rotary Bomb Oxidation Stability (D-2272)	250 minutes

(1) API Service Classifications for ashless GL-1, GL-2, GL-3

(2) Super high viscosity index and low pour point for wide temperature usage

(3) Fortified with food grade additives to resist wear, oxidation, rust and foam

This product is based on a proprietary and patented anti-oxidant, anti-wear, and cold flow technology. Base stocks are non-GMO agricultural vegetable oils. This stabilized technology provides high performance in high and low temperature applications, reducing oil thickening and deposits.

<sup>1</sup> Base oils and additives in this product are listed in 21 CFR 178.3570, Lubricants for incidental food contact (USDA H-1). Full compliance with other applicable restrictions of FDA, USDA, oil spill, and oil pollution prevention statutes is recommended.

#### To Order

Fax to 831-728-1753 or call 800-491-9473 for Customer Service

Visit [www.wisesolutions.net](http://www.wisesolutions.net) or Email [sales@wisesolutions.net](mailto:sales@wisesolutions.net)

Available Size  
Container

5 gal. Pail	55 gal. Drum	330 gal. Tote

Quantity (min.)